

1. grinding / sandblasting the surface to be coated



2. thorough cleaning of the surface by blowing and suction




GRIPS[®] BridgeCoat

LOGIS

Processing instructions **WITHOUT** adhesion promoter

3. mask off surfaces not to be coated with a 50 mm wide fabric tape



Attention:

The coating compound is applied in 2 passes.

1. Pass = base coat (consumption approx. 250 g/m²)
2. Pass = base course (consumption approx. 250 g/m²)

Due to the reaction time, the consumption quantities must be mixed separately for each layer.

Coating work with LCT S6691P must be carried out quickly and with good planning due to the rapid curing of the material (approx. 15 min).

Reference value for first processors 2.25 kg mixture (1.5 kg A + 0.75 kg B) for approx. 9 m²

GRIPS[®] BridgeCoat

LOGIS

Processing instructions **WITHOUT** adhesion promoter

4. Coating system LCT S6691P (mixing ratio 100:50 by weight)

4.1 Stir LCT S6691P part A mechanically



4.2 Then fill 50 parts B component into 100 parts A component



4.3 Stir both components well together (approx. 2 min)



GRIPS[®] BridgeCoat

LOGIS

Processing instructions **WITHOUT** adhesion promoter

5. application of the base coat
LCT S6691P by means of a short
pile roller

After application, allow to dry
for approx. 60 min.



GRIPS[®] BridgeCoat



LOGIS

Processing instructions **WITHOUT** adhesion promoter



6. repeat steps no. 4 and 5 for making the base course, but do not let it dry!

Continue immediately with step 7 →



GRIPS[®] BridgeCoat

LOGIS

Processing instructions **WITHOUT** adhesion promoter



7. Apply LOGIS GRANOFLOUR (Sanding) with a funnel gun on the damp floor.

Consumption: approx. 1.5 kg/m²



GRIPS[®] BridgeCoat

LOGIS

Processing instructions **WITHOUT** adhesion promoter

8. blow or suck off the excess sand from the surface that has dried free of adhesives.




As soon as the surface is free of adhesive, the fabric adhesive tape should be removed. Curing time until full load approx. 8 hours.



GRIPS® **BridgeCoat**

 LOGIS

Processing instructions WITHOUT adhesion promoter



Contact:
Logis Application Technology
info@logis.ag | +49 (0)8636 695900